

Package: KSA (via r-universe)

October 3, 2026

Type Package

Title Retained Component Criterion for Principal Component Analysis

Version 0.1.0

Date 2022-09-20

Author Fayed Alshammri

Maintainer Dr. Fayed Alshammri <fayed333@hotmail.com>

Description The Retained Component Criterion for Principal Component Analysis (RCC_PCA) is a tool to determine the optimal number of components to retain in PCA.

License GPL-2

Depends stats, graphics

Encoding UTF-8

RoxygenNote 7.2.1

NeedsCompilation no

Repository <https://aboaziz1.r-universe.dev>

Date/Publication 2022-09-21 21:20:06 UTC

RemoteUrl <https://github.com/cran/KSA>

RemoteRef HEAD

RemoteSha bceb2c2ebb767709bbec1d29cf2b3a49f9745670

Contents

RCC_PCA	2
Index	3

RCC_PCA

*Retained Component Criterion for Principal Component Analysis***Description**

The Retained Component Criterion for Principal Component Analysis (RCC_PCA) is build under the KSA backage, which is named after my home country the Kingdom of Saudi Arabia. The RCC_PCA criterion is a new tool to determine the optimal number of components (i.e. PCs) to retain for Principal Component Analysis (PCA). This criterion balances between the following two desires, reducing the dimension of the data and increasing the accuracy of the final results of PCA; See Alshammri (2022).

Usage

RCC_PCA(x)

Arguments

x a N-by-m data matrix, where the rows are "N" observations, and the columns are "m" variables

Value

The values of RCC criterion

Author(s)

Fayed Alshammri

References

Alshammri, F. (2022). Retained component criterion for optimizing principal component analysis. Manuscript submitted for publication.

Examples

```
##The data matrix x is the scaled first four variables of "iris data" with m=4 and N=150.
x=scale(iris[,1:4])

##calculate and plot the RCC_PCA values of x after applying PCA.
myresults=RCC_PCA(x)

##lists the values of RCC criterion
myresults
```

Index

RCC_PCA, [2](#)